



Color


Print - Web - Fabric




PANTONE 123 C
HEX # FFc72c
RGB 255, 199, 44
CMYK 0%, 19%, 89%, 0%



PANTONE 2995 C
HEX # 00A9E0
RGB 0, 169, 224
CMYK 83%, 1%, 0%, 0%




K TEXT
HEX # 272525
RGB 39, 37, 37
CMYK 0%, 0%, 0%, 100%



RICH BLACK
HEX # 000000
RGB 0, 0, 0
CMYK 60%, 50%, 50%, 100%


Color

Industrial Design



PANTONE PQ-1235C
 HEX # FFB81C
 RGB 255, 184, 28
 CMYK Values not available

Main Plastic




PANTONE PQ-299C
 HEX # 00A3E0
 RGB 0, 163, 224
 CMYK Values not available

Power / Backlight Button




PANTONE PQ-CoolGray6C
 HEX # A7A8AA
 RGB 167, 168, 170
 CMYK Values not available

Other Buttons / Controls



PANTONE PQ-CoolGray11C
 HEX # 53565A
 RGB 83, 86, 90
 CMYK Values not available

Overmolding / Rubber



RICH BLACK
 HEX # 000000
 RGB 0, 0, 0
 CMYK 60%, 50%, 50%, 100%

Text / Graphics

Product Textures

Housing, Buttons
 Light EDM, MT 11010

Exposed Metal Blocks
 Medium EDM, MT 11020

Overmolding / Rubber
 Heavy EDM, MT 1055

Typography

Heading 1

Titles - Crillee Bold Italic LET

Heading 2

Bold Headers - Myriad Pro / Black SemiExtended

Heading 3

Light Headers - Myriad Pro / SemiExtended Italic

Heading 4

Subheaders - Myriad Pro / Bold Condensed

Text 1

Myriad Pro / Regular

Fine Print 1


Fine Print - Myriad Pro / Condensed

Logo


Correct usage of the Primary Logo



No Tag Line



With Tag Line





Main Logo Font: **Crillee Bold Italic LET**
Tag Line Font: **Myriad Pro / Bold Condensed**

Do not use black and white logos with a Color image. B/W Only

Logo

Correct padding of the Primary Logo



 = 10% overall reduction of the base rectangle, or 1% of the volume.



Logo



Alone with no black flag background



Color logo on Rich Black only



On top of any color flag except Rich Black



Do not change the colors of the Canon and Name



Incorrect usage of the logo



Background flag too small



Background flag too big



Background flag not a rectangle

Logo

Correct usage of Secondary Logo


Fieldpiece®



PANTONE
123 C

Crillee Bold Italic LET

Fieldpiece®



PANTONE
Rich Black

Fieldpiece®



PANTONE
White

Logo



Correct usage of the Job Link logo



Usage

Examples of Logo in Advertising

JL3 Pressure



JL3 Psychrometer



JL3 Pipe Clamp





Free Mobile App



Job Link® System Wireless Probes

350' Wireless Range

- Strong signal goes through walk-ins

JL3 Pressures

- Fits in tight spaces with 45° angled fitting

2 Kits available JL3KR4 and JL3KH6
www.fieldpiece.com

JL3 Psychrometers

- Flexible wand with heavy duty magnet

JL3 Pipe Clamps

- Extremely accurate and fast reacting



Free Mobile App

**Amazing distance.
No suit needed.**





Free Mobile App



Job Link® System Probes

Fieldpiece wireless probes are designed for agility and speed with a **wireless range of 350'**. And it's powerful enough to transmit into space. Well, not really, but it will go through walk-ins! The Pressure probes fit in tight places. Rapid Rail™ sensor stabilizes pipe temps in 3 seconds, the psychrometer's flex probe and magnet make it easy to get air measurements from anywhere. Now available at your local distributor.






www.FieldpieceJoblink.com

AHR Booth #5746

Usage



Dual port manometer with industry exclusive pressure switch tester

- Gas, static, and differential pressure
- Easily calibrate any adjustable pressure switch
- Great for diagnosing furnace performance



714-634-1844
www.Fieldpiece.com
Instagram Facebook Twitter

Examples of Logo in Advertising

NEW! Inspection Tool Bag

Page 1

Feb 27 2018



HVACR Inspection Tool Bag

The New BG36 Inspection Tool Bag is an easy to carry, over the shoulder bag with an easy to open pop top. The pop top protects tools from inclement weather, and from spilling out if dropped or knocked over. Plus it provides extra space for small tools and drill bits. The strong magnetic tray holds cabinet screws and washers so they're never lost.

Sectioned interior pockets keep everything organized. Zippered side pocket and large interior adjustable section protect meters from hand tools. Large open front pocket and expandable side pockets allow for additional storage. Sturdy weather protected base keeps bag standing upright.

BG36 Inspection Tool Bag

Distributor Cost (2pc)	\$61.88
Suggested Trade	\$99.00

- Quick locking magnetic closure
- Weather protected sturdy base
- Isolated pockets for test instruments
- Handy magnetic tray



Check out our Pre-Order
Special, and order yours
Today!

details on page 2

tel: 714-634-1844
fax: 714-551-2299
e-mail: orders@fieldpiece.com

If you do not wish to receive any further/fax messages from Fieldpiece, please fax 714 551 2299 with your fax number and the word "REMOVE" written somewhere on the page. Or call us at 714 634 1844. If you wish to be removed from our list via an email message, please email fpmarketing@fieldpiece.com with the subject line "REMOVE" followed by your fax number.

Job Link® System

Wireless Probes

350ft RANGE



350' Wireless Range
• Powerful signal goes through walk-ins

JL3 Psychrometers
• Flexible wand with heavy duty magnet

JL3 Pipe Clamps
• Extremely accurate and fast reacting

JL3 Pressures
• Fits in tight spaces with 45° angled



714-634-1844
www.Fieldpiece.com



Packaging

Example of Packaging



Packaging

Example of Packaging

Tools HVACR Pros Trust

SM480V Specs

Feature	Spec
Refrigerant	For R410A, R418A and R418B (not for use with other refrigerants)
Pressure Range	0 to 100 psig (0 to 7 bar) (0 to 1000 kPa)
Accuracy	±0.5% (0 to 100 psig)
Display	4.3" Color LCD
Connect Type	1/2" NPT (1/2" NPT) (1/2" NPT)
Dimensions	4.5" H x 3.5" W x 2.5" D (114 x 89 x 64 mm)
Weight	1.5 lbs (0.7 kg)
Operating Temp	32°F to 140°F (0°C to 60°C)
Storage Temp	-20°F to 140°F (-3°C to 60°C)

Designed for Performance

Knowledge, power and experience are packed into the newly designed SMAN™ Refrigerant Manifold. Years of feedback from A/C and refrigeration specialists is combined with Fieldpiece's laser focus on continuous improvement to bring you the toughest, most advanced digital refrigerant manifold on the market. From the extremely rugged overmold casing, reinforced hook, and hermetically sealed sight glass, to the wireless capabilities, data logging, and lightness test, the SM480V 4 port manifold is built so you can do your job easier, faster and better.

Connect Traditionally

View Job Link® System Tools

Connect to Job Link App

What's Included

- SM480V SMAN Refrigerant Manifold (4 Port)
- (1) TC24 Type K Free-Range Thermocouples
- (1) ATAT1 Type K Biased Thermocouple w/Clip
- (1) ANCI1 Padded Carrying Case
- (1) Job Link

What's Included

- SM480V SMAN Refrigerant Manifold (4 Port)
- (1) TC24 Type K Free-Range Thermocouples
- (1) ATAT1 Type K Biased Thermocouple w/Clip
- (1) ANCI1 Padded Carrying Case
- (1) Job Link

SMAN™ Refrigerant Manifold and Micron Gauge

SM480V

Packed with Knowledge

The SM480V is designed to work the way you do with advanced features like data logging, system tightness test, direct connection to the Job Link App, and user customization.

Customizable

- Adjust auto power off duration
- Adjust back light duration
- Set high and low vacuum alarms
- Favorite frequently used refrigerants

Tightness Test

- Check for leaks after repairs to installations
- View pressure differential over time
- Timer tracks duration of test
- Temperature/pressure compensated to avoid false positives

Data Logging

- Stores up to 9 jobs internally
- Easy download via USB port
- Displays % free storage space before logging begins
- Logs up to 7 days (168 continuous hours)
- Screen shuts down after three hours to save battery life
- Program intervals between 1 sec and 2 min

Job Link® System Integration

- Live pipe and air temps with Job Link probes
- Monitor refrigerant weight directly on SMAN using SRS3 scale
- View measurements on SMAN and/or in Job Link App
- Direct 300' wireless range (no transmitter needed)

Simply Strong

Years of knowledge and in-field use are the driving forces behind the SM480V's heavy duty construction. Extra rugged casing, reinforced hook, water resistance, and extra roomy padded hanging case ensure the latest SMAN manifolds withstand the rigors of field use.

Water Resistant (IP54)

Impact Resistant Case

3 Protected Thermocouple Jacks

Built-in Micron Gauge

3/8" VAC Port

Beefy Hook

DO MORE

www.fieldpiece.com

Packaging

Example of Packaging

Easy, Long Range, Powerful

Take a full system installation quickly and easily with the JL3KH6 Charge and Air Test Kit. The kit consists of 2 pressure probes, 2 pipe clamps, and 2 psychrometers in a quick access padded case. All measurements can be sent up to 550' away directly to your mobile device with the Job Link™ app. Each tool is designed for safety and speed. The pressure probes fit in tight spaces. The pipe clamps use the new Rapid Rail™ sensor design delivering accuracy, speed, and agility, even on the most awkward pipe configurations. The psychrometer features narrow probes and configurable magnets making it easy to measure supply returns, ducts, and returned registers. Do more with Job Link™, please!

Powerful Wireless Signal Strength

- Up to 550' wireless signal
- Powerful enough to go through most walls in coolers and freezers
- Battery lifetime to your mobile device

Rapid Rail™ Sensor Advantages

- Stabilizes in under a second
- Beeper and LED indicate adequate connection
- The Rapid Rail™ sensor seals pipe to complete circuit so ambient conditions don't affect the measurement
- Narrow jaws connects in tight spaces and on irregular pipe shapes

Reliable Pressures Regardless of Location

- 45° angled fitting easily connects in tight spaces
- Pressure sensors are accurate at any elevation
- Calibrates automatically when powered on

Configurable Psychrometric Testing

- Probes measure return and supply for gases and registers
- Place at multiple locations based on system requirements
- Long flexible probe with holding magnet for easy placement on system
- Narrow lip fits in 3/8" return register
- Real time airway and delivered BTUs

Tools HVACR Pros Trust
Proven reliability for 40+ years
It's a legend known all over

Fieldpiece
Tools HVACR Pros Trust
Proven reliability for 40+ years
It's a legend known all over

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

Flex Psychrometer Versatility

The narrow flexible probe with magnetic hanger gives you the power to get air temperature hands-free with confidence. Place probes in critical locations based on system needs with long range wireless signal.

The Job Link™ App Advantages

Send live measurements directly to your mobile device up to 550' away and see how the indoor and outdoor units are working together. Email a professional report with your company details and any job notes.

DO MORE

Quick-Access Case
Store the probes safely in the lined padded case. Quickly pop open the top and set up your tools.

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

Fieldpiece

Tools HVACR Pros Trust

Full System Snapshot

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

DO MORE

Quick-Access Case
Store the probes safely in the lined padded case. Quickly pop open the top and set up your tools.

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

Fieldpiece

Tools HVACR Pros Trust

Full System Snapshot

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

DO MORE

Quick-Access Case
Store the probes safely in the lined padded case. Quickly pop open the top and set up your tools.

Wireless Charge and Air Test Kit Job Link™ Probes JL3KH6

RIGHT STUFF

45° Angled Pressure Fittings
Connects easily in tight places and odd angles.

Rapid Rail™ Sensor Benefits

The patent pending Rapid Rail™ sensor is lighting quick and accurate even in hot and sticky conditions. The LED and beeper indicate when you have an accurate connection with the pipe.